




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b> <b>A61N 5/06</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/41767</b> <b>(43) International Publication Date:</b> 20 July 2000 (20.07.00)
<b>(21) International Application Number:</b> PCT/SE00/00044 <b>(22) International Filing Date:</b> 13 January 2000 (13.01.00) <b>(30) Priority Data:</b> 9900074-7      13 January 1999 (13.01.99)      SE <b>(71) Applicant (for all designated States except US):</b> BIOLIGHT PATENT HOLDING AB [SE/SE]; Svärdvägen 15, S-182 33 Danderyd (SE). <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> THIBERG, Rolf [SE/SE]; Åkersbergavägen 10, S-184 50 Åkersberga (SE). <b>(74) Agents:</b> ÖRTENBLAD, Bertil et al.; Noréns Patentbyrå AB, P.O. Box 10198, S-100 55 Stockholm (SE).		<b>(81) Designated States:</b> AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i> <i>In English translation (filed in Swedish).</i>

**(54) Title:** APPARATUS FOR ADMINISTERING EXTERNAL TREATMENT WITH THE AID OF LIGHT**(57) Abstract**

Apparatus for external medical treatment administered with the aid of light, said apparatus including a light-emitting device (1) which is intended to be held against or in the close proximity of the patient's body, and means (8, 9, 10) for driving the light-emitting device, wherein the light-emitting device includes light-emitting diodes or corresponding elements adapted to emit monochromatic light, wherein the drive means (8, 9, 10) is adapted to cause the light-emitting device (1) to emit one or more types of monochromatic light over one or more predetermined time periods and to pulsate the light emitted in accordance with a predetermined pulse frequency or series of pulse frequencies over said time periods, wherein said drive means (8, 9, 10) includes a computer (8) and circuits (9, 10) for driving the light-emitting diodes (3, 4), wherein the computer (8) includes input means (13, 16) for inputting data relating to an intended treatment, wherein the computer (8) is adapted to deliver electric signals to the drive circuits (9, 10), wherewith intended light-emitting diodes (3, 4) function to emit light within predetermined time periods and at predetermined pulse repetition frequencies. The invention is characterised in that at least the drive circuits (9, 10) of the drive means are mounted in the light emitting device (1).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

APPARATUS FOR ADMINISTERING EXTERNAL TREATMENT WITH THE AID  
OF LIGHT

5 The present invention relates to an apparatus for external medical treatment with the aid of light, more specifically with the aid of light which palliates and/or cures different states of diseases.

10 Swedish Patent Specification No. 502 784 for example teaches an apparatus for external medical treatment with the aid of light that includes a light emitting device which is intended to be held against or close to the body of an individual, and drive means for operating the light emitting device, said device including light emitting diodes or corresponding  
15 elements which are intended to emit infrared light. According to the aforesaid patent specification, the means for driving the light emitting device is designed to control said device to emit infrared light in a first stage over a first predetermined time period and then to emit visible light in a  
20 second stage over a second predetermined time period, wherein said drive means is adapted to control the light emitting device to pulsate the infrared light and the visible light in accordance with a predetermined series of pulse frequencies.

25 It is also known to emit other monochromatic light for treating different states of diseases.

It has also been found that very good results can be obtained when treating a patient with solely one or more types of  
30 monochromatic light and with light other than infrared light, such as visible light of different colours emitted in accordance with a given pulse frequency.

It has been found that a device of the aforesaid kind can be used very successfully for treating many different states of diseases, wounds and injuries, for instance sport sustained injuries, stretched muscles, muscular pain, joint pain, headaches, various inflammatory conditions, various skin complaints, such as acne, back pains, etc., provided that the light is emitted in a certain way. In this regard, treatment with light has a favourable influence on injury healing processes and will palliate and/or cure various diseases.

There is thus an understanding that treatment with certain light that is emitted in certain frequency series will have a significantly greater effect in shortening the time taken to cure or palliate a disease.

One problem with known apparatus of the present kind is that voltage is applied to the light emitting device, which is intended to be held against or in the close proximity of the patient's body, through a cable extending from a separate device in the form of a drive means which includes computer circuits and associated drive circuits for activating the light emitting diodes in said light emitting device. The apparatus is therefore relatively expensive and clumsy.

This problem is solved by the invention

The present invention thus relates to an apparatus for controlling external medical treatment administered with the aid of light, wherein the apparatus includes a light emitting device which is intended to be held against or in the close proximity of the patient's body, and drive means for operating the light emitting device, wherein said light emitting device includes light emitting diodes or corresponding elements that emit monochromatic light, wherein

said drive means is designed to control the light emitting device to emit one or more types of monochromatic light over one or more predetermined time periods and to pulsate the light emitted in accordance with a predetermined pulse frequency or series of pulse frequencies over said time periods, wherein said drive means includes a computer and diode drive circuits, wherein the computer includes an input means for the input of data relating to the treatment concerned, wherein the computer is programmed to deliver electric signals to the drive circuits and wherein activated light emitting diodes emit light within predetermined time periods and at predetermined pulse repetition frequencies, and wherein the apparatus is characterised in that at least the drive circuits of said drive means are mounted in the light emitting device.

The invention will now be described in more detail by way of example, partly in connection with an embodiment of the invention shown in the accompanying drawings, in which

- Figure 1 is a schematic block diagram illustrating apparatus of the present kind;
- Figure 2 is a side view of a light emitting device;
- Figure 3 is a block diagram illustrating an apparatus according to a first embodiment of the invention;
- Figure 4 is a block diagram illustrating a second embodiment of the inventive apparatus; and
- Figure 5 illustrates one embodiment of the light emitting device of Figure 2 from above.

Figures 1 and 2 illustrate generally an apparatus for external medical treatment with the aid of light, said apparatus including a light emitting device 1 which is intended to be held against or in the close proximity of the patient's body. The light emitting device is shown from one

side in Figure 2 and from beneath in Figure 1. This device includes a casing 5 which houses a transparent plate 6. Located beneath the plate 6 is a surface 2 on which a plurality of light emitting diodes 3, 4 or corresponding elements are mounted.

The light emitting diodes thus emit light through the plate 6 when energised, i.e. when supplied with current through a cable 7.

10

When the device is being used, the casing 5 is held so that the plate 6 will lie against the relevant part of the patient's body.

15 The apparatus also includes drive means for operating the light emitting device 1. The drive means is designed to control the light emitting device 1 to emit different monochromatic light of different wavelengths over different predetermined time periods, and to pulsate the light emitted  
20 in accordance with a predetermined pulse frequency or series of pulse frequencies over said time periods.

The light emitting device 1 may include light emitting diodes 3 which emit infrared light. These diodes are shown with  
25 solid circles in Figure 1. Visible light can be emitted with the aid of other light emitting diodes 4. These diodes are illustrated with empty circles in Figure 1. The infrared light diodes 3 will preferably be semi-conductors of the GaAs-type (Gallium Arsenide). The diodes 4 that emit visible  
30 light will also preferably be of the GaAs-type.

The drive means includes a computer 8 which controls drive circuits to which signals for driving or operating the light emitting diodes are sent from the computer via a conductor.

The cable 7, which includes the conductor, may for instance have a length of from one to three metres and extends between the drive means and the light emitting device 1. The drive  
5 means will have a size that corresponds generally to the size of a standard personal computer.

The computer and the drive circuits are of a suitable known kind. The drive means or computer has connected thereto a  
10 keyboard 13 by means of which the operator can key-in data for causing the drive means to activate the light emitting device in a desired manner. The apparatus will conveniently also include a display 14 for displaying the settings entered through the keyboard. This display may be the computer  
15 screen.

The light emitting device 1 includes light emitting diodes 4 which are adapted to emit essentially monochromatic visible light in one of the colours violet, blue, yellow, orange, red  
20 or green, and also infrared light and other invisible wavelengths.

The nature of the light used will depend on the disease or the type of injury to be treated.

25 A large part of the above description of the drawings is also found to a great part in the aforementioned patent specification.

30 According to the present invention at least the drive circuits 9, 10 of the drive means are mounted in the light emitting device 1. This means that a separate and specially adapted drive means of the aforescribed kind is not required but can be replaced with other means.

According to a first embodiment of the invention, the computer 8 is a personal computer or corresponding device and is free-standing in relation to the light emitting device.

5 The computer is programmed to deliver a coded signal to a microprocessor 12 or corresponding device in the light emitting device via a conductor 11, said microprocessor functioning to activate or energise the drive circuits 9, 10 subsequent to decoding the signal; see Figure 3.

10

In this embodiment of the invention, the computer, which may be any type of commercially available PC, is programmed with a program that controls the computer to send to the microprocessor 12 coded signals that correspond to the treatment to be administered. The microprocessor 12 includes a memory and is permanently programmed to decode the coded signals and therewith activate the drive circuits 9, 10 which, in turn, activate the light emitting diodes 3, 4 in accordance with the treatment desired. The coded signals are transmitted to the light emitting device 1 through a cable 7. Electric current is supplied to the light emitting device 1 through a conductor 20 connected to a battery eliminator 19, to which a mains voltage is applied.

25 In this way, the necessary specific equipment has been reduced to include the light emitting device and the electronics incorporated therein, and a computer program that shall be read into a computer.

30 Figure 4 illustrates a second embodiment of the invention in which the computer 8 is integrated with the light emitting device 1. The computer 8 of this embodiment will conveniently have the form of a microprocessor and associated memory. The computer 8 is programmed to activate the light emitting

diodes via the drive circuits 9, 10, such as to carry out different treatments. The various treatments desired can be fed into the computer via a suitable input means. The input means 15 of the computer 8 is disposed in the light emitting device. As illustrated in Figure 5, a preferred method is to arrange a known, simple keypad 16 and associated display 17 on the light emitting device 1.

According to this embodiment it is achieved that all of the equipment is accommodated in the light emitting device, wherewith said device need only be supplied with current via a conductor 18 and a battery eliminator 19.

It will be obvious that the present equipment is both cheaper and less bulky than the known equipment. This enables the equipment to be moved more easily between different treatment stations, among other things.

Although the invention has been described with reference to a number of exemplifying embodiments, it will be understood that the invention can be varied in many ways. For instance, the light emitting device can be powered through the same lead as the cable 7. The apparatus may also include more than two drive circuits. Moreover, the drive means may be designed to effect solely one given type of treatment, by emitting one or more types of monochromatic light over given time periods and with given pulse repetition frequencies.

The present invention is therefore not limited to the aforescribed embodiments, since variations can be made within the scope of the following Claims.

## CLAIMS

1. Apparatus for controlling external medical treatment administered with the aid of light, said apparatus including  
5 a light-emitting device (1) which is intended to be held against or in the close proximity of the patient's body, and means (8, 9, 10) for driving the light-emitting device, wherein the light-emitting device includes light-emitting diodes or corresponding elements adapted to emit  
10 monochromatic light, wherein the drive means (8, 9, 10) is adapted to cause the light-emitting device (1) to emit one or more types of monochromatic light over one or more predetermined time periods and to pulsate the light emitted in accordance with a predetermined pulse frequency or series  
15 of pulse frequencies over said time periods, wherein said drive means (8, 9, 10) includes a computer (8) and circuits (9, 10) for the light-emitting diodes (3, 4), wherein the computer (8) includes input means (13,16) for inputting data relating to an intended treatment, wherein the computer (8)  
20 is adapted to deliver electric signals to the drive circuits (9, 10), wherewith intended light-emitting diodes (3, 4) function to emit light within predetermined time periods and at predetermined pulse repetition frequencies, characterised in that at least the drive circuits (9, 10) of the drive  
25 means are mounted in the light emitting device (1).

2. Apparatus according to Claim 1, characterised in that the computer (8) is a personal computer or a corresponding device and is free-standing in relation to the light emitting  
30 device (1); in that the computer (8) is adapted to send a coded signal to a microprocessor (12) or corresponding device in the light emitting device (1) via a conductor (7), wherewith the microprocessor (12) functions to activate said drive circuits (9, 10) subsequent to decoding said signal.

3. Apparatus according to Claim 1, characterised in that the computer (8) is integrated in the light emitting device (1).

5

4. Apparatus according to Claim 3, characterised in that the infeed means (16) of the computer (8) is disposed in the light emitting device.

1 / 2

Fig. 1




Fig. 2





Fig. 3



2 / 2

Fig. 4





Fig. 5



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00044

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A61N 5/06

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A61N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 9746279 A1 (BIOLIGHT PATENT HOLDING AB), 11 December 1997 (11.12.97), page 2, line 10 - line 29, abstract	1-4
	--	
A	US 5500009 A (EMANUEL MENDES ET AL), 19 March 1996 (19.03.96), column 2, line 64 - column 3, line 13, abstract	1-4
	-- -----	

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

18 February 2000

Date of mailing of the international search report

15-05-2000

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Lotta Gunnarsson/mj

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT  
Information on patent family members

02/12/99

International application No.

PCT/SE 00/00044

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9746279 A1	11/12/97	AU 3113997 A	05/01/98
		CA 2257394 A	11/12/97
		EP 0904133 A	31/03/99
		SE 509003 C	23/11/98
		SE 9602272 A	08/12/97
<hr/>			
US 5500009 A	19/03/96	CA 2120457 A	28/03/95
		US 5259380 A	09/11/93
		US 5549660 A	27/08/96
<hr/>			